DROP FORGED BLANK ROD ENDS

Drop forged. Listed diameters and lengths carried in stock blank, self-colored. Drilling, threading, other machining and plating furnished to specification.



NOTE: Average properties of 1035 natural hot rolled steel 75/85,000 lbs. P.S.I. tensile, 40/55,000 lbs. P.S.I yield.

USA +	D ROP I	FORGED	DLANK	KOD E	NDS		
	Stock	Part No.	Dimensions – Inches				Weight
	No.		Shank Diameter (B)	Boss Diameter (C)	Boss Thickness (F)	*Length (A) in Inches	Per 100
1	C-134	18005 4	1/4"	1/2"	9/32"	3"	6.1
	C-134-A	18010 8	1/4"	1/2"	9/32"	6"	11
	C-135	18015 3	5/16"	5/8"	11/32"	3"	9.5
	C-135-A	18020 7	5/16"	5/8"	11/32"	6"	18
	C-163-A	18025 2	3/8"	11/16"	3/8"	2-1/8"	12
	C-162	18030 6	3/8"	3/4"	3/8"	2-1/2"	12.5
	C-217	18035 1	3/8"	3/4"	7/16"	3"	14
	C-136	18040 5	3/8"	3/4"	7/16"	6"	25.5
ά 🔶	C-137	18045 0	7/16"	7/8"	1/2"	6"	35
-l = l-	C-245	18050 4	1/2"	15/16"	9/16"	1-3/4"	22
itt'↓	C-163	18055 9	1/2"	15/16"	9/16"	3-1/8"	27.5
	C-212	18060 3	1/2"	1"	9/16"	3-1/2"	30
	C-138	18065 8	1/2"	1"	9/16"	6"	47
HT I	C-195	18070 2	1/2"	1"	9/16"	10"	70
	C-189	18075 7	5/8"	1-1/4"	11/16"	3"	45.5
11	C-303	18080 1	5/8"	1-3/16"	5/8"	3-1/2"	48
il	C-139	18085 6	5/8"	1-1/4"	11/16"	6"	77.5
	C-172	18090 0	5/8"	1-1/4"	11/16"	8"	92
1	C-196	18095 5	5/8"	1-1/4"	11/16"	10"	119
	C-216	18100 6	3/4"	1-1/2"	13/16"	3-1/2"	82
Ψ	C-140	18105 1	3/4"	1-1/2"	13/16"	6"	112
	C-197	18110 5	3/4"	1-1/2"	13/16"	10"	163.5
	C-141	18115 0	7/8"	1-3/4"	15/16"	6"	164
s also	C-211	18120 4	7/8"	1-3/4"	15/16"	12"	377
Stainless	C-142	18125 9	1"	2"	1-1/16"	6"	216
e page 48.	C-142-A	18130 3	1"	2"	1-1/16"	12"	354
	C-282	18135 8	1-1/4"	2-1/2"	1-5/16"	12"	595

BLACK OXIDE MACHINED ROD ENDS (MADE IN USA)

	Thread Pitch	Dimensions – Inches						
Part No.		Length in Inches (A)*	Thread Length (T)	Hole I.D. (G)	Boss Diameter (C)	Boss Thickness (F)	Weight Per 100	
18205 8	1/4"-20	2"	3/4"	3/16"	1/2"	9/32"	4	
18210 2	5/16"-18	3"	1-1/2"	5/16"	5/8"	11/32"	8	
18215 7	3/8"-16	3"	1-1/2"	5/16"	3/4"	7/16"	12	
18220 1	3/8"-16	3"	1-1/2"	3/8"	3/4"	7/16"	12	
18225 6	3/8"-16	3-3/4"	2"	3/8"	3/4"	7/16"	14	
18230 0	3/8"-16	4"	1-1/2"	3/8"	3/4"	7/16"	16	
18235 5	3/8"-16	5"	2-1/2"	3/8"	3/4"	7/16"	18	
18245 4	1/2"-13	3-3/4"	1-1/2"	3/8"	1"	9/16"	29	
18250 8	1/2"-13	4"	1-1/2"	3/8"	1"	9/16"	30	
18240 9	1/2"-13	5"	1-1/2"	3/8"	1"	9/16"	36	
18255 3	1/2"-13	5"	2"	3/8"	1"	9/16"	36	
18260 7	5/8"-11	4-1/2"	2"	5/8"	1-1/4"	11/16"	50	
18265 2	5/8"-11	5"	1-3/4"	5/8"	1-1/4"	11/16"	55	
18270 6	5/8"-11	6"	2-1/2"	5/8"	1-1/4"	11/16"	63	
18280 5	3/4"-10	4-1/2"	2"	3/4"	1-1/2"	13/16"	77	
18275 1	3/4"-10	6"	2-1/2"	3/4"	1-1/2"	13/16"	95	
Measured fr	om center of t	oss						