

## **ROUND BASE - WITH PROJECTIONS**

FASTENERS & COMPONENTS





| ROUND BASE WELD NUTS WITH PROJECTIONS |                |               |      |                 |      |               |      |                     |                   |      |                       |      |
|---------------------------------------|----------------|---------------|------|-----------------|------|---------------|------|---------------------|-------------------|------|-----------------------|------|
| Part Number                           | Thread<br>Size | Н             |      | W               |      | В             |      | N                   | Р                 |      | т                     |      |
|                                       |                | Barrel Height |      | Barrel Diameter |      | Base Diameter |      | Projection<br>Width | Projection Height |      | Material<br>Thickness |      |
|                                       |                | Max           | Min  | Max             | Min  | Max           | Min  | ± 1/32              | Max               | Min  | Max                   | Min  |
| 0804NWRP                              | 8-32           | .281          | .219 | .224            | .194 | .750          | .688 | 7/64                | .046              | .016 | .046                  | .016 |
| 10093NWRP                             | 10-24          | .312          | .250 | .258            | .228 | .781          | .719 | 7/64                | .054              | .024 | .054                  | .024 |
| 11093NWRP                             | 10-32          | .312          | .250 | .258            | .228 | .781          | .719 | 7/64                | .054              | .024 | .054                  | .024 |
| 1405NWRP                              | 1/4-20         | .344          | .281 | .320            | .290 | .781          | .719 | 7/64                | .054              | .024 | .062                  | .032 |
| 1407NWRP                              | 1/4-20         | .469          | .406 | .320            | .290 | .781          | .719 | 7/64                | .054              | .024 | .062                  | .032 |



| EASTEN                      |  |  |  |  |  |  |  |
|-----------------------------|--|--|--|--|--|--|--|
| Description                 | Internally threaded barrel-shaped fasteners integrally formed with a circular, flat base that has three dome-shaped protrusions on its top side. |  |  |  |  |  |  |
| Applications/<br>Advantages | An economical welding fastener used when it is neccesary to restrict the nut from rotating when tightened.                                       |  |  |  |  |  |  |
| Material                    | Cold rolled steel  |  |  |  |  |  |  |
|                             |  |  |  |  |  |  |  |

